

MATERIAL SAFETY DATA SHEET

Manufacturer's Name: Viper Products
Address: 87 Sachem Dr
Middletown ,Ct 06457
Phone: 800-942-8754
Emergency Number: Chemtrec (800) 424-9300/OVERSEAS (703) 527-3887

SECTION I - PRODUCT INFORMATION

Product Name: DV Pro-coat Blended with Pigments (Standard colors)

HMIS/NFPA RATINGS: HEALTH: 1 FIRE: 2 REACTIVITY: 0 SPECIFIC HAZARDS: NONE

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENT	OSHA PEL	ACGIH TLV	OPTIONAL %
Pigments are blended 20 % with 80 % Top coat Blend			
Propylene Glycol Methyl Ethelr CAS #107-98-2	Not Established	100 ppm	<4.0
N-Methyl-2-Pyrrolidone CAS #872-50-4	Non Established	Not Established	<3.0
Ethylene Glycol N-Butyl Ether	50 ppm (skin)	25 ppm (skin)	<2.0

SECTION III -PHYSICAL/CHEMICAL CHARACTERISTICS

MELTING POINT: Liquid
BOILING POINT: 212oF (100C)
VAPOR DENSITY (AIR=1): >1
SOLUBILITY IN WATER: Soluble
APPEARANCE: Semi Translucent

SPECIFIC GRAVITY (H2O-1): 1.01
VAPOR PRESSURE (mm Hg): Not Measured
EVAPORATION RATE (BUTYL ACETATE=1): <1.0
PERCENT VOLATILES BY WEIGHT : Apprx. 79%
V.O.C.: 0.73 lbs/gal. 8.62% of Total Weight

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >140F (60C) FLAMMABLE LIMITS: Not Determined
FLAMMABILITY CLASSIFICATION -OSHA: Combustible Class IIIB
EXTINGUISHING MEDIA: Foam, Water fog, Dry Chemical, or CO2
UNUSUAL FIRE AND EXPLOSION HAZARDS: None Known
SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should be equipped with self-contained breathing apparatus and turnout gear

SECTION V - REACTIVITY DATA

STABILITY: x STABLE
UNSTABLE

INCOMPATIBILITY: Oxidizing Material
HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may produce Carbon Dioxide and Carbon Monoxide
HAZARDOUS POLYMERIZATION: MAY OCCUR
x WILL NOT OCCUR

CONDITIONS TO AVOID: None Known

SECTION V I- HEALTH HAZARD DATA

PRIMARY ROUTE(S) OF ENTRY: INHALATION? Yes SKIN? Yes INGESTION? Yes
CARCINOGEN: NTP? No IARC MOMGRAPHS? No OSHA REGULATED? No
EFFECTS OF OVEREXPOSURE: For Ethylene glycoln butyl Ether: **Eye Contact:** May cause moderate eye irritation. May cause corneal injury. **Skin Contact:** May cause skin irritation. Excessive exposure may cause blood hermolysis. **Inhalation:** Excessive inhalation may cause adverse effects including blood and kidney.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None Known
EMERGENCY FIRST AID PROCEDURES: **Inhalation:** Move subject to fresh air. If difficulty breathing, administer Oxygen. Seek Medical attention. **Eyes:** Irrigate with running water for at least 15 minutes. Consult medical personnel.

Skin: Wash affected areas with soap and water. Consult a physician if irritation persists. **Ingestion:** Induce vomiting, Seek medical attention.

SECTION VII- PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled: Spill should be contained and the product absorbed with absorbent material and collected for disposal.

Waste disposal method: Dispose in accordance with local, state, and federal regulations.

Precautions to be taken in handling and storage: Protect from freezing. Keep container closed.

Other Precautions: For Industrial Use Only

SECTION VIII - CONTROL MEASURES

VENTILATION: General and Local Exhaust to control airborne levels below exposure guidelines.

PROTECTIVE GLOVES: Impervious gloves required.

EYE PROTECTION: For splash protection - Chemical goggles required

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: As necessary to prevent skin contact. Eye wash station nearby.

WORK/HYGIENIC/MAINTENANCE PRACTICE: Wash after use.

SECTION IX -REGULATORY INFORMATION

TOXIC SUBSTANCE CONTROL ACT (TSCA)

All components of this product are listed or are exempt from listing on the U.S. Toxic Substance Control Act (TSCA) Chemical Substance Inventory; 40 CFR 723.250 Section V.

SARA313

This product contains the following chemicals subject to the reporting of SARA Title III Section 313 40CFR372.

<u>CHEMICAL</u>	<u>CAS NO.</u>
Ethylene Glycol N-Butyl Ether	111-76-2
N-Methyl-2-Pyrrolidone	872-50-4